



Technical data

Portable hand-operated 3-phase starter for D-O-L start of pumps with thermal contacts built-in.

Type:	START 351
Voltage:	3 x 500 V
Frequency:	50-60 Hz
Current range:	1,0 - 32 A
Overload protection:	Thermal/magnetic overload protection
Monitoring:	Monitoring of thermal contacts with manual reset Phase sequence indicator
Connection supply:	CEE-plug 4-pole 32 A, 500V
Connection pump:	Terminal connection with cable glands
General:	Degree of protection IP54 Size 285 x 110 x 95 mm Weight 0,8 kg CE-marked

Type	Voltage (V)	Current range (A)	Type of supply connection	Pump cable Ø (mm)	Part no.
START 351-500-B-432- 1,6 2,5 4 6 10 14 18 23 25 32	3 x 500	1,0 - 1,6	CEE plug 4-pole 32 A 3P + E	11 - 21	554 30 70
		1,6 - 2,5		-"-	554 30 71
		2,5 - 4,0		-"-	554 30 72
		4 - 6,3		-"-	554 30 73
		6 - 10		-"-	554 30 74
		9 - 14		-"-	554 30 75
		13 - 18		-"-	554 30 76
		17 - 23		-"-	554 30 77
		20 - 25		-"-	554 30 78
		24 - 32		18 - 25	554 30 79