



Technical data

Portable hand-operated 3-phase starter for D-O-L start of pumps with thermal contacts. Special design for the North American market. CSA-approved.

Type:	START 356-600-B-PG-XX
Voltage:	Max 600 V
Frequency:	50-60 Hz
Monitoring:	Thermal/magnetic overload protection Monitoring relay for thermal contacts
Connection supply:	Terminal connection 1,5-6 mm ² , with cable glands
Connection pump:	Terminal connection 1,5-6 mm ² , with cable glands
Current range:	1,0 - 25 A
General:	Degree of protection IP55 Size 255 x 168 x 100 mm Weight 2,7 kg Approved by CSA

Type	Voltage (V)	Current range (A)	Supply cable Ø (mm)	Pump cable Ø (mm)	Part no.
START 356-600-B-PG-1,6	600	1,0 - 1,6	13 - 20	18 - 25	554 21 00
-"	2,5	-"	-"	-"	554 21 01
-"	4	-"	-"	-"	554 21 02
-"	6	-"	-"	-"	554 21 03
-"	10	-"	-"	-"	554 21 04
-"	14	-"	-"	-"	554 21 05
-"	18	-"	-"	-"	554 21 06
-"	23	-"	-"	-"	554 21 07
-"	25	-"	-"	-"	554 21 08